



Wall-mounted i25 captures 180° field of view – no blind spots.

Perfect Wall Mount. Compact and Discrete.

The i25 is a 6MP hemispheric camera and is perfectly suited to be wall mounted with a tilt angle of 15 degree to achieve the best panoramic overview of a room without any blind spots. One i25 captures an entire room, easily replacing four standard cameras. The newly-designed wall mount form factor fits into every environment.



Lens tilted down 15 deg.

Perfect Fit

The i25 can be wall mounted onto any surface. The small form factor matches perfectly with any environment. For fast installations, simply use the optional cavity installation set. A surface mount kit for concrete walls, for example, is available as well.



Ideal for Wall Mounting

The i25 hemispheric model will be wall mounted with a tilt angle of 15 degree to achieve a perfect panoramic overview of a room. If mounted above the door, the i25 looks even partially underneath or into the door. A 103° model is available too.



HD Audio Package (optional)

All 6MP indoor models are available upon request with an integrated HD audio package (microphone and speaker in the camera housing). In addition to video recording with sound, the audio functionality can also be used for making announcements in sales or exhibition rooms, or for automatically playing an alarm signal when the camera-integrated sensor is triggered to scare off undesired visitors.

Technical Data

Lens Options	B016, B036	Min. Light Sensitivity	Day Sensor: 0.1 lux at 1/60 sec
Image Sensors	1/1.8" CMOS (6MP), Day (Color)	Sensor Resolution	6MP: 3072x2048 pixels (Color)
Max. Frame Rate (MxPEG)	MEGA/HD: 30 fps, QXGA: 15 fps, 6MP: 8 fps	Compression	MxPEG, M-JPEG, JPEG, H.264 (SIP video only)
DVR Recording	Internal: microSD Card External: PC/NAS (to 4 TB)	Audio (optional)	VoIP, sound recording using audio package
Operating Conditions	IP30, 0 to +40 °C	Internal Sensors	Temperature, illumination, shock detector
Image Processing	MxActivitySensor, VMD, image correction, backlight, MxAnalytics	Software (free of charge)	MxManagementCenter, MOBOTIX App

Accessory Options

The detachable MxBus-IO-Module is an extension of the system accessories for the indoor camera line. Connected to a MOBOTIX indoor camera, the module with 2 self-powered inputs and 2 outputs allows to access MxBus and the connection of external sensors or the switching of relays.



Need Assistance?

Please contact Suretek Pty Ltd for wholesale pricing and free expert advice on the entire MOBOTIX range. Suretek Pty Ltd is an authorised MOBOTIX Distributor and Solutions Partner.

W: www.suretek.com.au • T: 1300 65 44 33 • ipvideo@suretek.com.au