



Adjustable lens modules can capture two different areas simultaneously.

## Versatile. Twice as Vigilant.

The D15 is a dual-sensor dome camera with two lens modules providing a wide range of fully adjustable viewing options for a huge variety of applications. The D15 is completely modular and can be setup as standard DualDome, as 180° model with super-wide panorama field of view or as day-night version.

### D15 – Modular Fixdome with Two Lens Units

The D15 is able to secure two different areas simultaneously. The key advantage of the D15 is its manually adjustable lens configuration and the completely modular structure. Once installed, the lens units can be fixed into any position.



Adjustable Lens Model

### Flexible Installation


The D15 is characterized by complete modularity. Choose from available lens carriers (pano, fix), lens units, all fully adjustable in any direction within the camera. This flexibility, combined with the dual-lens system, provides practically unlimited viewing options from one camera.



Fixed Lens Model

### Day & Night Capture

The D15 body can be also equipped with a day&night carrier, which provides parallel alignment of two lenses for perfect same-view day and night video capture.



### Two Cameras in One

Dual-lens system captures two different views simultaneously and requires only a single PoE cable connection.

Technical Data			
<b>Lens Options</b>	B036 to B237, 180° version (panorama), DNight-FIX version with parallel Day/Night lenses	<b>Min. Light Sensitivity</b>	Day Sensor: 0.1 lux at 1/60 sec Night Sensor: 0.02 lux at 1/60 sec
<b>Image Sensors</b>	1/1.8" CMOS (6MP) Day (Color) or Night (B&W)	<b>Sensor Resolution</b>	6MP: 3072x2048 pixels (Color/B&W)
<b>Max. Frame Rate (MxPEG)</b>	MEGA/HD: 30 fps, QXGA: 15 fps, 6MP: 8 fps, 2x 6MP: 4 fps	<b>Compression</b>	MxPEG, M-JPEG, JPEG, H.264 (SIP video only)
<b>DVR Recording</b>	Internal: microSD Card External: PC/NAS (to 4 TB)	<b>Audio</b>	Integrated microphone & speaker, VoIP, intercom, sound recording
<b>Operating Conditions</b>	IP65/54 (with/without wall mount), IK10, IP66/IK10+ (with Vandalism Kit), -30 to +60 °C	<b>Internal Sensors</b>	Temperature, PIR, microphone illumination, shock detector
<b>Image Processing</b>	MxActivitySensor, VMD, image correction, backlight	<b>Software (free of charge)</b>	MxManagementCenter, MOBOTIX App

### D15 Lens Units



The D15 camera can house a max. of two manoeuvrable Lens Units that come in standard Day/Color or Night Black/White for lowlight applications. In most of the D15 models the Lens Units are not pre-installed so need to be ordered separately. Please contact Suretek for advice on which Lens Units will be best for your installation.

### Need Assistance?

Please contact Suretek Pty Ltd for wholesale pricing and free expert advice on the entire MOBOTIX range. Suretek Pty Ltd is an authorised MOBOTIX Distributor and Solutions Partner.

W: [www.suretek.com.au](http://www.suretek.com.au) • T: 1300 65 44 33 • [ipvideo@suretek.com.au](mailto:ipvideo@suretek.com.au)